

Technical Specifications

	TROY				ASPEN (II)					ASPEN (II) GELATO				ASPEN (II) PASTRY				ASPEN (II) COMBO		ASPEN (II) CORNER				
	T12-G	T16-G	T18-G	T24-G	T12-P	T16-P	T18-P	T24-P	TROY S	A(II)12-G	A(II)16-G	A(II)18-G	A(II)20-G	A(II)24-G	A(II)12-P	A(II)16-P	A(II)18-P	A(II)20-P	A(II)24-P	A(II)20-C	A(II)24-C	A(II)Corner		
LENGTH	millimeters	1225	1559	1732	2251	1225	1559	1732	2251	...	1255	1575	1765	1975	2325	1255	1575	1765	1975	2325	1975	2325	...	
	inches	48.23'	61.38'	68.19'	88.62'	48.23'	61.38'	68.19'	88.62'	...	49.90'	62'	69.49'	77.76'	91.54'	49.40'	62'	69.49'	77.76'	91.54'	77.76'	91.54'	...	
DEPTH	millimeters	1190	1190	1190	1190	1245	1245	1245	1245	1190	1140	1140	1140	1140	1140	1150	1150	1150	1150	1150	1150	1150	1140	
	inches	46.85'	46.85'	46.85'	46.85'	49'	49'	49'	49'	46.85'	44.88'	44.88'	44.88'	44.88'	44.88'	45.28'	45.28'	45.28'	45.28'	45.28'	45.28'	45.28'	44.88'	
HEIGHT	millimeters	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	1380	
	inches	54.33'	54.33'	54.33'	54.33'	54.33'	54.33'	54.33'	54.33'	54.33'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	54.3'	
WEIGHT	Net Kg.	250	370	397	460	240	330	357	420	246	295	440	460	485	525	300	350	375	400	450	406	525	260	
	Gross Kg.	330	455	490	580	320	420	450	540	316	400	560	590	610	655	405	465	490	520	570	525	575	335	
CAPACITY OF PANS		12x5Lt. 8x7Lt.	16x5Lt. 10x7Lt.	18x5Lt. 12x7Lt.	24x5Lt. 16x7Lt.	11x5Lt. 9x5Lt.						10x5Lt.	12x5Lt.	13 Pans: 9x5Lt. 4x6Lt.		
POWER OF COMPRESSORS		1130W	782+700W	782+782W	1130+782W	490W	580W	630W	1170W	1400W	1130W	782+700W	782+782W	1130+782W	1130+782W	490W	580W	630W	780W	1170W	1130+490W	1130+490W	1400W	
REFRIGERANT		R404a	R404a	R404a	R404a	R134a	R134a	R134a	R134a	R404a	R404a	R404a	R404a	R404a	R404a	R134a	R134a	R134a	R134a	R134a	R404a+R134a	R404a+R134a	R404a	
RUNNING TEMPERATURE AT 35C / 95F, 60% AT 35C AT 95F		-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	-15/-20C 5/-4F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	-18/-22C 0/-7.6F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	+4/+8C +39/+46F	(-18/-22C) (+4/+8C) (0/-7.6F) (+39/+46F)	(-18/-22C) (+4/+8C) (0/-7.6F) (+39/+46F)	-15/-20C 5/-4F
RELATIVE HUMIDITY																								
POWER SUPPLY		220/1/ 50-60Hz 400/3/50-60Hz	220/1/ 50-60Hz 400/3/50-60Hz	220/1/ 50-60Hz 400/3/50-60Hz	220/1/ 50-60Hz 400/3/50-60Hz	220/1/ 50-60Hz	220/1/ 50-60Hz	220/1/ 50-60Hz	220/1/ 50-60Hz	220/1/ 50-60Hz 400/3/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/50-60Hz	220/1/ 50-60Hz or 400/3/50-60Hz	
COMPRESSOR TYPE		HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	HERMETIC	
REFRIGERATION SYSTEM		FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	FORCED AIR	
DEFROSTING		AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	AUTOMATIC	
DEFROSTING TYPE		HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	RESISTANCE	RESISTANCE	RESISTANCE	RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	RESISTANCE	RESISTANCE	RESISTANCE	RESISTANCE	RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	HOT GAS + RESISTANCE	

